

## **Foreword**

The formulation of this national standard was initiated by the Agricultural Machinery Testing and Evaluation Center (AMTEC) through the project “Multicrop Processing Machines for `Commercialization” funded by the Department of Science and Technology (DOST) through its Technology Innovation for Commercialization (TECHNICOM) Program and monitored by the Philippine Council for Agriculture, Forestry and Natural Resources Research and Development (PCARRD).

This standard has been technically prepared in accordance with BPS Directives Part 3:2003 – Rules for the Structure and Drafting of International Standards.

The word “shall” is used to indicate mandatory requirements to conform to the standard.

The word “should” is used to indicate that among several possibilities one is recommended as particularly suitable without mentioning or excluding others.

In the preparation of this standard, the following documents/publications were considered:

AMTEC Test and Evaluation Report MARVEL Corn Mill Model MCM 8-10

AMTEC Test and Evaluation Report SULTANA Rice/Corn Mill (For Corn) Model: SM-1.8

AMTEC Test and Evaluation Report VIRIÑA Hammer mill (for arrow root)

ASAE Standard: ASAE S319.1 Method of Determining and Expressing Fineness of Feed Materials By Sieving

Bautista, O. K. and H. B. Aycardo. Ginger: Its Production, Handling, Processing and Marketing with Emphasis on Export. Department of Horticulture, College of Agriculture, University of the Philippines Los Baños. 1979.

CIGR Handbook of Agricultural Engineering- Volume IV- Agro-Processing Engineering. Published by American Society of Agricultural Engineers. 1999.

Malinis, Arnulfo P., et al. Development of the Integrated Multicrop Processing System (Zero Waste Ginger Processing Technology). 2004.

PAES 226:2005 Agricultural Machinery – Micromill-Specifications

<b>CONTENTS</b>		<b>Page</b>
<b>1</b>	Scope	79
<b>2</b>	References	79
<b>3</b>	Definitions	79
<b>4</b>	General Conditions for Test and Inspection	80
<b>4.1</b>	Selection of multicrop micromill to be tested	80
<b>4.2</b>	Role of manufacturer/dealer	81
<b>4.3</b>	Role of the Operator	81
<b>4.4</b>	Test site conditions	81
<b>4.5</b>	Termination of test	81
<b>5</b>	Test Preparation	81
<b>5.1</b>	Test Instrument	81
<b>5.2</b>	Test Material	81
<b>5.3</b>	Sample Preparation	81
<b>5.4</b>	Running-in and Preliminary Adjustment	81
<b>6</b>	Pre-test Observation	82
<b>6.1</b>	Verification of the Manufacturer's technical data and information	82
<b>7</b>	Performance Test	82
<b>7.1</b>	Operation of the multicrop micromill	82
<b>7.2</b>	Test trial	82
<b>7.3</b>	Test material Sampling	82
<b>7.4</b>	Data Collection	82
<b>7.5</b>	Data recording and observations	83
<b>8</b>	Laboratory Analysis	83
<b>9</b>	Formula	84
<b>10</b>	Test Report	84

**ANNEXES**

<b>A</b>	Minimum List of Field and Laboratory Test Equipment and Materials	85
<b>B</b>	Specifications of Multicrop Micromill	86
<b>C</b>	Performance Test Data Sheet	88
<b>D</b>	Laboratory Test Data Sheet	90
<b>E</b>	Formula Used During Calculation and Testing	91

**Agricultural Machinery – Multicrop Micromill – Methods of Test**

---

**1 Scope**

This standard specifies the methods of test and inspection for multicrop micro mill used for grinding/milling of dried meals of ginger, arrow root, taro, cassava, sweet potato, potato, carrot, onion, garlic, pandan and lemon grass.

- 1.1** verify the mechanism, dimensions, materials, accessories of the multicrop micromill and the list of specifications submitted by the manufacturer;
- 1.2** determine the performance of the machine;
- 1.3** evaluate the ease of handling and safety features
- 1.4** analyze the products of milling/grinding through laboratory analysis; and
- 1.5** report the results of the tests.

**2 References**

The following normative documents contain provisions, which through reference in this text constitute provisions of these standards:

ASTM E11 - Specifications for Wire-Cloth Sieves for Testing Purposes

PAES 103:2000 Agricultural Machinery – Method of Sampling

PAES 238:2008 Agricultural Machinery – Multicrop Micromill- Specifications

**3 Definitions**

For the purpose of this standard, the definitions given in PAES 238 and the following shall apply:

**3.1****fineness**

indicates the uniformity of grind in the resultant product

**3.2****input capacity**

weight of input test material per unit time, expressed in kilogram per hour

### **3.3**

#### **input time**

time required to empty the hopper from full load per trial

### **3.4**

#### **labor requirement**

number of man-day needed in the operation of the multicrop micromill

### **3.5**

#### **milling capacity**

total amount of materials milled over the total time the multicrop micromill is in operation, expressed in kilogram per hour

### **3.6**

#### **milling efficiency**

ratio between the amount of acceptable ground/milled product and the total milling recovery, expressed in percentage

### **3.7**

#### **milling recovery**

ratio between the total amount of ground/milled product recovered and the total input materials, expressed in percentage

### **3.8**

#### **operating time**

actual milling operation of the machine

### **3.9**

#### **prime mover**

electric motor or internal combustion engine used to drive the machine

### **3.10**

#### **quality**

refers to the fineness of the ground/milled product

### **3.11**

#### **running-in period**

preliminary operation of the machine to make final adjustments prior to the conduct of test

### **3.12**

#### **sealed**

free of openings that allow the entry or passage of moisture

## **4 General Conditions for Test and Inspection**

### **4.1 Selection of multicrop micromill to be tested**

Machine submitted for test shall be sampled in accordance with PAES 103.

#### **4.2 Role of manufacturer/dealer**

The manufacturer shall submit specifications and other relevant information about the multicrop micromill and shall abide with the terms and conditions set forth by an official testing agency.

#### **4.3 Role of the operator**

An officially designated operator shall be skilled and shall demonstrate, operate, adjust, and repair as the case maybe, related to the operation of the machine.

#### **4.4 Test site conditions**

The site should have ample provisions for material handling, temporary storage and workspace and suitable for normal working conditions.

#### **4.5 Termination of Test**

If during testing, the machine stops due to major component breakdown or malfunctions, the test engineer from the official testing agency shall terminate the test.

### **5 Test Preparation**

#### **5.1 Test instruments**

The instruments to be used shall have been calibrated and checked by the testing agency prior to the measurements. The suggested list of minimum field and laboratory test equipment and materials needed to carry out the multicrop micromill test is shown in Annex A.

#### **5.2 Test material**

Test materials to be used shall be any of the following crops; dried meals of ginger, arrow root, taro, cassava, sweet potato, potato, carrot, onion, garlic, pandan and lemon grass with the following characteristics:

##### **5.2.1 Test material characteristics**

**5.2.1.1 Variety** : locally grown (as much as possible single variety)

**5.2.1.2 Condition** : dried

**5.2.1.3 Moisture Content** : 12 -14 %

##### **5.2.1.4 Quantity to be supplied**

The amount of test material that will be used in performing the test shall be at least 75 % of the input capacity.

#### **5.3 Sample Preparation**

Prepare the test material in such a way that the test sample for each trial shall have identical characteristics in terms of variety and condition. Care should be taken so as to prevent alterations of the conditions of the test materials.

#### **5.4 Running-in and preliminary adjustment**

Before the start of the test, the multicrop micromill should have undergone running-in period wherein various adjustments of the multicrop micromill shall be made according to the

recommendation of the manufacturer. No other adjustments shall be permitted while the test is on-going.

## **6 Pre-test Observation**

### **6.1 Verification of the manufacturer's technical data and information**

This inspection is carried out to verify the mechanism, dimensions, materials and accessories of the multicrop micromill in comparison with the list of manufacturer's technical data and information.

**6.2** A plain and level surface shall be used as reference plane for verification of multicrop micromill dimensional specifications.

**6.3** The items to be inspected and verified shall be recorded in Annex B.

## **7 Performance test**

This is carried out to obtain actual data on overall machine performance.

### **7.1 Operation of the multicrop micromill**

The multicrop micromill shall be operated at the recommended settings of the manufacturer. After each test trial, the milling area shall be cleaned and then prepared for the next test trial.

### **7.2 Test Trial**

A minimum of three (3) test trials, with duration of at least 15 minutes per trial, shall be adopted.

### **7.3 Sampling**

#### **7.3.1 Sampling procedure for test materials**

Before each test trial, randomly take three (3) 100-gram samples for determination of initial moisture content.

#### **7.3.2 Sampling from the collecting bin**

After each test trial, three (3) 250-gram samples shall be randomly collected from the collecting bin of the multicrop micromill to be analyzed in the laboratory.

#### **7.3.3 Handling of Samples**

All samples shall be placed in appropriate containers, properly labeled and sealed.

### **7.4 Data Collection**

#### **7.4.1 Duration of Test**

The duration of each test trial shall start from loading of test materials into the hopper and ends after all the milled products are collected in the collecting bin.

#### **7.4.2 Noise level**

The noise emitted by the machine shall be measured using a noise level meter at the location of the operator and collector. The noise level shall be measured approximately 50 mm away from the ear level of the operator and collector.

#### **7.4.3 Speed of Components**

The speed of the rotating shafts of the major components of the multicrop micromill shall be taken using tachometer.

NOTE Measurements shall be taken with and without load for sub-clauses 7.4.2 and 7.4.3 as specified in Annex C. Measurements with load shall be randomly taken during the duration of each test trial.

#### **7.4.4 Fuel/Power Consumption**

Before the start of each trial, the fuel tank shall be filled to its capacity for internal combustion engines used as power source. After each test trial the tank shall be refilled using graduated cylinder. The amount of refueling is the fuel consumption for the test. When filling up the tank, keep the tank horizontal so as not to leave empty space in the tank.

In case an electric motor is used as the prime mover, a power meter shall be used to measure electric energy consumption. Measurement shall be randomly taken during the duration of each test trial.

#### **7.5 Data recording and observations**

Record sheet for all data and information during the test is given in Annex C.

### **8 Laboratory Analysis**

Laboratory analysis shall be made to determine moisture content and fineness of test material. The laboratory test data sheet to be used is given in Annex D.

#### **8.1 Moisture Content**

This shall be taken following the standard procedures for oven-dry method (wet basis).

**8.1.1** For each test trial, select three (3) representative samples weighing at least 25 g of test materials and place them in the moisture can. The moisture cans shall be sealed to ensure that no moisture is lost or gained by the samples between the times they were weighed. Record the initial weight.

**8.1.2** Dry the samples in the oven with temperature of 103 °C – 105 °C for at least 24 hours.

**8.1.3** After removing the samples from the oven, it should be placed in desiccators and allowed to cool to ambient temperature.

**8.1.4** Weigh each moisture cans including the dried sample. Record the final weight. Calculate the moisture content using the equation in Annex E.

#### **8.2 Analysis of Ground Product**

This shall be taken using Sieve Shaker Testing. A set of sieves as specified in ASTM E11 - Specifications for Wire-Cloth Sieves for Testing Purposes shall be used.

**8.2.1** For each test trial, place the samples in a testing sieve shaker with a series of sieves screen.

**8.2.2** Shake the samples for at least 5 minutes.

**8.2.3** After shaking, remove the samples from each sieve screen. Weigh and record each weight.

**8.2.4** Calculate the percent of ground/milled materials retained on each sieve screen.

**8.2.5** Calculate the milling efficiency as follows:

**8.2.5.1** For seasoning purposes, the percent of material retained on the 50 mesh sieve screen shall be used in the computation.

**8.2.5.2** For flour purposes, the percent of materials retained on the pan shall be used in the computation.

## **9 Formula**

The formulas to be used during calculations and testing are given in Annex E.

## **10 Test Report**

The test report shall include the following information in the order given:

**10.1** Title

**10.2** Summary

**10.3** Purpose and Scope of Test

**10.4** Methods of Test

**10.5** Description of the Machine

Table 1 – Machine Specifications

**10.6** Results and Discussions

**10.7** Observations (include pictures)

Table 2 –Performance test data

**10.8** Name/s, signature/s and designation of test engineers



**Annex A**  
(informative)

**Minimum List of Field and Laboratory  
Test Equipment and Materials**

<b>A.1</b>	<b>Equipment</b>	<b>Quantity</b>
<b>A.1.1</b>	<b>Field</b>	
<b>A.1.1.1</b>	Tachometer (contact type or photo electric type) Range: 0 rpm to 5,000 rpm	1
<b>A.1.1.2</b>	Digital timers (range: 60 minutes) Accuracy: 0.1 sec	2
<b>A.1.1.3</b>	Tape measure (with maximum length of 5m)	1
<b>A.1.1.4</b>	Noise level meter Range: 30 dB (A) to 130 dB (A)	1
<b>A.1.1.5</b>	Portable digital scale (capacity: 100 kg) Scale divisions: 500 g or Weighing scale (capacity: 100 kg) Scale divisions: 500 g	1
<b>A.1.1.6</b>	Graduated cylinder (for engines) (500 ml capacity) or power meter (for electric motors) 60 Hz, 220 V	1
<b>A.1.1.7</b>	Camera	1
<b>A.1.1.8</b>	Vernier Caliper Accuracy: 0.1 mm	1
<b>A.1.2</b>	<b>Laboratory</b>	
<b>A.1.2.1</b>	Air Oven	1
<b>A.1.2.2</b>	Sieve Shaker	1
<b>A.1.2.3</b>	Electronic Balance Sensitivity: 0.1 g	1
<b>A.1.2.4</b>	Desiccators	
<b>A.1.2.5</b>	Sieves Screen ASTM E-11 #12, #16, #20, #30, #40, #50, Pan	
<b>A.2</b>	<b>Materials</b>	
<b>A.2.1</b>	Moisture cans	
<b>A.2.2</b>	Sample bags	
<b>A.2.3</b>	Labeling tags which include	
<b>A.2.3.1</b>	Date of test	
<b>A.2.3.2</b>	Multicrop micromill on test	
<b>A.2.3.3</b>	Sample source	
<b>A.2.3.4</b>	Variety	
<b>A.2.3.5</b>	Trial number	

**Annex B**  
(informative)

**Specifications of Multicrop Micromill**

Name of Applicant/ Distributor: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 Tel No: \_\_\_\_\_  
 Name of Manufacturer: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 Tel No: \_\_\_\_\_

**GENERAL INFORMATION**

Make: \_\_\_\_\_ Type: \_\_\_\_\_  
 Serial No: \_\_\_\_\_ Brand/Model: \_\_\_\_\_  
 Production date of Multicrop Micromill to be tested: \_\_\_\_\_  
 Testing Agency: \_\_\_\_\_ Test Engineer: \_\_\_\_\_  
 Date of Test: \_\_\_\_\_ Location of Test: \_\_\_\_\_

**Items to be inspected**

ITEMS	Manufacturer's Specification	Verification by the Testing agency
<b>B.1</b> Main structure		
<b>B.1.1</b> Overall dimensions, mm		
<b>B.1.1.1</b> length		
<b>B.1.1.2</b> width		
<b>B.1.1.3</b> height		
<b>B.1.2</b> Weight, without prime mover (kg), if applicable		
<b>B.2</b> Hopper		
<b>B.2.1</b> Material		
<b>B.2.2</b> Thickness, mm		
<b>B.2.3</b> Height from the ground, mm		
<b>B.2.4</b> Location		
<b>B.3</b> Power Transmission		
<b>B.3.1</b> Pulley		
<b>B.3.1.1</b> Type		
<b>B.3.1.2</b> Dimension, mm		
<b>B.3.1.2</b> Speed Reducer Input Shaft		
<b>B.3.1.2.1</b> Type		
<b>B.3.1.2.2</b> Dimension, mm		
<b>B.3.1.2.3</b> Speed Ratio		
<b>B.4</b> Main Frame		
<b>B.4.1</b> Material		
<b>B.4.2</b> Thickness, mm		
<b>B.4.3</b> Dimension, mm		
<b>B.5</b> Milling Chamber		
<b>B.5.1</b> Hammer mill type		
<b>B.5.1.1</b> Material		

<b>B.5.1.2</b>	Number of beater		
<b>B.5.2</b>	Attrition mill type		
<b>B.5.2.1</b>	Plate used		
<b>B.5.2.2</b>	Material		
<b>B.5.2.3</b>	Diameter, mm		
<b>B.5.2.4</b>	Thickness, mm		
<b>B.5.3</b>	Roller mill type		
<b>B.5.3.1</b>	Number of rollers		
<b>B.5.3.2</b>	Length, mm		
<b>B.5.3.3</b>	Diameter, mm		
<b>B.6</b>	Screen		
<b>B.6.1</b>	Mesh Number		
<b>B.6.2</b>	Material		
<b>B.7</b>	Cyclone		
<b>B.7.1</b>	Material		
<b>B.8</b>	Collecting bin		
<b>B.8.1</b>	Material		
<b>B.8.2</b>	Dimension, mm		
<b>B.9</b>	Prime mover		
<b>B.9.1</b>	Electric motor		
<b>B.9.1.1</b>	Brand		
<b>B.9.1.2</b>	Make or manufacturer		
<b>B.9.1.3</b>	Serial No.		
<b>B.9.1.4</b>	Type		
<b>B.9.1.5</b>	Rated Power, kW		
<b>B.9.1.6</b>	Rated Speed, rpm		
<b>B.9.1.7</b>	Frequency, Hz		
<b>B.9.1.8</b>	Voltage		
<b>B.9.1.9</b>	Weight, kg		
<b>B.9.2</b>	Engine		
<b>B.9.2.1</b>	Brand		
<b>B.9.2.2</b>	Model		
<b>B.9.2.3</b>	Make or manufacturer		
<b>B.9.2.4</b>	Serial No.		
<b>B.9.2.5</b>	Type		
<b>B.9.2.6</b>	Rated Power, kW		
<b>B.9.2.7</b>	Rated Speed, rpm		
<b>B.9.2.8</b>	Displacement (cm <sup>3</sup> )		
<b>B.9.2.9</b>	Cooling system		
<b>B.9.2.10</b>	Starting system		
<b>B.9.2.11</b>	Weight, kg		

**Annex C**  
(informative)

**Performance Test Data Sheet**

Test Trial No. \_\_\_\_\_ Date: \_\_\_\_\_  
 Test Engineer: \_\_\_\_\_ Location: \_\_\_\_\_  
 Assistants: \_\_\_\_\_ Test Specimen: \_\_\_\_\_  
 Test Requested by: \_\_\_\_\_ Manufacturer: \_\_\_\_\_

<b>C.1</b> Information on the Test Materials					
<b>C.1.1</b>	Crop				
<b>C.1.2</b>	Source				
<b>C.1.3</b>	Moisture Content				
<b>C.2</b> Result of Performance Test					
	<b>ITEMS</b>	<b>Trial 1</b>	<b>Trial 2</b>	<b>Trial 3</b>	<b>Ave.</b>
<b>C.2.1</b>	Weight of Input, kg				
<b>C.2.2</b>	Input time, s				
<b>C.2.3</b>	Input Capacity, kg				
<b>C.2.4</b>	Operating time, s				
<b>C.2.5</b>	Milling capacity, kg/h				
<b>C.2.6</b>	Milling recovery, %				
<b>C.2.7</b>	Milling efficiency, %				
<b>C.2.8</b>	Speed of Components, rpm				
<b>C.2.8.1</b>	Electric Motor				
<b>C.2.8.1.1</b>	Without load				
<b>C.2.8.1.2</b>	With load				
<b>C.2.8.2</b>	Main Shaft				
<b>C.2.8.2.1</b>	Without load				
<b>C.2.8.2.2</b>	With load				
<b>C.2.8.3</b>	Prime mover Shaft				
<b>C.2.8.3.1</b>	Without load				
<b>C.2.8.3.2</b>	With load				
<b>C.2.9</b>	Noise Level, dB(A)				
<b>C.2.9.1</b>	Without load				
<b>C.2.9.2</b>	With load				
<b>C.2.10</b>	Power Consumption				
<b>C.2.10.1</b>	Power, kW				
<b>C.2.10.1.1</b>	Without load				
<b>C.2.10.1.2</b>	With load				
<b>C.2.10.2</b>	Voltage, V				
<b>C.2.10.2.1</b>	Without load				
<b>C.2.10.2.2</b>	With load				
<b>C.2.10.3</b>	Current, A				
<b>C.2.10.3.1</b>	Without load				
<b>C.2.10.3.2</b>	With load				
<b>C.2.11</b>	Fuel consumption				
<b>C.2.11.1</b>	Fuel time, h				
<b>C.2.11.2</b>	Fuel consumed, L				

**C.3 Rate the following observations:**

Items	Rating*				
	1	2	3	4	5
C.3.1 Ease of loading					
C.3.2 Ease of cleaning parts					
C.3.3 Ease of adjusting and repair of parts					
C.3.4 Ease of collecting output					
C.3.5 Ease of transporting the machine					
C.3.6 Safety					
C.3.7 Vibration					

- \*1 – Very good
- 2 - Good
- 3 - Satisfactory
- 4 - Poor
- 5 – Very poor

**C.4 Other Observations:**

---

---

---

**Annex D**  
(informative)

**Laboratory Test Data Sheet**

Machine Tested: \_\_\_\_\_

Analyzed by: \_\_\_\_\_

**D.1 Determination of Moisture Content**

Sample Material	Initial Weight, $W_{is}$				Final Weight, $W_{fs}$				% MC			
	Trial 1	Trial 2	Trial 3	Ave	Trial 1	Trial 2	Trial 3	Ave	Trial 1	Trial 2	Trial 3	Ave
Crop used												
Input test material meal												

**D.2 Analysis of Ground/Milled Product**

ASTM E11 Standard Testing Sieve	Weight of Material Retained			Percent of Material Retained		
	Trial 1	Trial 2	Trial 3	Trial 1	Trial 2	Trial 3
12						
16						
20						
30						
40						
50						
pan						
Total						

**Annex E**  
(informative)

**Formula Used During Calculations and Testing**

**E.1 Input Capacity,  $C_i$  (kg/h)**

$$C_i = \frac{W_i}{T_i}$$

where:

$C_i$	=	Input capacity, kg/h
$W_i$	=	Weight of input material, kg
$T_i$	=	Input time, h

**E.2. Milling Capacity,  $C_M$  (kg/h)**

$$C_M = \frac{W_o}{T_o}$$

Where:

$C_M$	=	Milling Capacity, kg/h
$W_o$	=	Total weight of ground material, kg
$T_o$	=	Total operating time, h

**E.3 Milling recovery, MR (%)**

$$MR = \frac{\text{Total ground/milled product, kg}}{\text{Total weight of input material, kg}} \times 100$$

**E.4 Milling efficiency, Eff (%)**

$$Eff = \frac{FP, \%}{MR, \%} \times 100$$

where:

Eff	=	milling efficiency, %
FP	=	Fine milled product (percent of materials retained on 50 mesh sieve screen for food seasoning purposes)
	=	Fine milled product (percent of materials retained on the pan for flour purposes)
MR	=	Milling recovery, %

**E.5 Moisture Content, MC (%)**

$$MC = \frac{W_{is} - W_{fs}}{W_{is}} \times 100$$

where:

MC	=	moisture content, %
W <sub>is</sub>	=	initial weight of samples, g
W <sub>fs</sub>	=	final weight of samples, g

## **E.6 Fuel/Electrical energy consumption**

### **E.6.1 Electrical energy consumption, E<sub>c</sub> (kW-h/kg)**

$$E_c = \frac{PcTo}{W_i}$$

where

E <sub>c</sub>	=	Electrical energy consumption, kW-h/kg
P <sub>c</sub>	=	Power consumed, kW
T	=	Time of operation, h
W <sub>i</sub>	=	Total weight of input, kg

### **E.6.2 Fuel consumption, F<sub>c</sub> (L/h)**

$$F_c = \frac{F_1}{T}$$

where:

F <sub>c</sub>	=	Fuel consumption, L/h
F <sub>1</sub>	=	Amount of fuel consumed, L
T	=	Time of operation, h