

Agricultural Machinery Testing and Evaluation Center 1977

ACR 002:2021 CHECKLIST AND REMINDERS FOR THE AMTEC TEST CONDITIONS AND REQUIREMENTS FOR WALKING-TYPE AGRICULTURAL TRACTOR (FLOAT-ASSIST TYPE)

■ Application for AMTEC Test
The test applicant shall submit AMTEC-OP-F01 (Agricultural Machinery Test Application Form) together with
the following requirements:
□ AMTEC-OP-16 (Waiver for Machine Specifications)
□ AMTEC-OP-18 (Data Privacy Consent Form)
■ Technical Specifications of the Machine
The test applicant shall submit any document/s indicating the specifications and other relevant information
of the machine upon application for testing.
□ Operator's manual with complete specifications as indicated in Annex B of PAES 111:2000
☐ Brochure
☐ Machine specifications sheet (shall be filled out upon request and receipt of copy from AMTEC in
case the manual or brochure is not available)
■ Preparation and Operation of the Machine
During field performance test, the tractor shall be ready for operation. The officially designated representative and/or operator of the test applicant shall operate, demonstrate, adjust, repair, and decide on matters related to the operation of the machine. The operator shall be skilled in operating a float-assist type walking-type agricultural tractor.
During laboratory performance test, the same tractor (including the engine) tested in the field shall be delivered to AMTEC. AMTEC shall handle and operate the machine during the laboratory testing proper.
■ Running-in of the Machine
A test run shall be conducted prior to the official test to check its condition and make necessary
adjustments to the machine. During field performance test, no other adjustments shall be permitted while
the official test is on-going.
■ Test Plot
The test applicant shall prepare at least three (3) test plots. Each test plot: ☐ Shall be at least 500 m² to the edges and rectangular with sides in the ratio of 2:1 as much as possible; ☐ Shall be soaked for at least 24 hours for wetland/lowland field (A 1 m wooden stick must penetrate
12-18 cm deep to the soil);
□ Shall have standing water with a depth of 3-5 cm; and
\square Shall be plowed if secondary tillage is the intended operation.
■ Other Test Necessities
The following shall also be adequately supplied during the conduct of the field performance test:
□ Fuel tank filled to full capacity;
□ 4 L or sufficient fuel for refilling after each test trial; and
□ Tools for machine repair and adjustments.
■ Machine Setting
The tractor shall be tested at the manufacturer's and the following recommended setting during rotary
tilling operation:
□ Forward speed range, kph: 2.5-4


☐ Operating depth, mm:100-120




Agricultural Machinery Testing and Evaluation Center 1977

■ Recommended Tilling Pattern

Circuitous pattern should be used during the field performance test operation.





■ Requirements

AMTEC shall conduct various tests and verification on different parameters of the machine including the following requirements as per PAES 124:2002:

Requirement as per PAES 124:2002 the tarctor shall be generally made of steel materials. or tractors powered by 3.73-5.22 kW gasoline engines, at least ISO
,
or tractors nowared by 2.72.5.22 kW aggeling angines, at least ISO
chain number (cn) 10A-1 (ANSI cn 50) shall be used. or tractors with engines greater than 5.22 kW power, ISO cn 12A-1
ANSI cn 60) shall be used.
shall be made of steel pipe.
shall have a minimum wall thickness and outside diameter of 3 mm and 25 mm, respectively.
shall be accessible to the operator's right-hand side.
shall be accessible to the operator's left-hand side.
elt guard shall be provided for operator's safety.
Mechanism for transmission belt adjustment shall be provided.
Mechanism for handle bar height adjustment shall be provided.
Mechanism for automatic disengagement of power transmission hall be provided.
:H C A

Standard Tools

Three (3) open wrenches, one (1) Philips screwdriver, one (1) flat screwdriver, one (1) adjustable wrench, and other basic tools shall be provided for the tractor. These tools shall be suitable to the necessary adjustment operations during maintenance and operation.

Workmanship and Finish	
Item	Requirement as per PAES 124:2002
General	☐ The tractor shall be free from manufacturing defects.
	☐ Any uncoated metallic surfaces shall be free from rust and shall be painted properly.
	☐ The tractor should be free from sharp edges and surfaces to avoid
	injuries.



Agricultural Machinery Testing and Evaluation Center 1977

■ Performance Requirements		
Criteria	Requirement as per PAES 124:2002	
Peak Transmission	80	
Efficiency, %, minimum	00	
Noise Level, dB(A),	92 (Allowable noise level for 6 hours of continuous exposure based on	
minimum	Occupation Safety and Health Standards, Ministry of Labor, Philippines, 1983)	
Field Capacity, %	As per manufacturer's specification	
Continuous Running	Shall have no breakdowns/malfunctions during the 5-hour test	

Suspension and Termination of Test

If the test plot does not conform with the recommended quantity and characteristics, AMTEC shall not proceed with the test. Should the test applicant request the conduct of the test despite the non-conformity to the test requirements identified by AMTEC, the applicant shall sign the AMTEC Waiver for Nonconformity to Test Requirements.

☐ AMTEC-OP-F24 (Waiver for Nonconformity to Test Requirements)

If the machine stops due to breakdown or malfunction during the test run affecting the machine's performance, the test may be suspended. If the machine cannot continue the operation, the test shall be consequently terminated.

■ Other Assistance During Test

- 1. For field and laboratory tests outside the AMTEC premises, the applicant shall shoulder the transportation expenses (i.e. fuel, toll fees, vehicle rental, plane fare, sea fare, etc.) of the AMTEC Staff assigned for the testing activity.
- 2. The applicant is requested to assist the AMTEC Staff in looking and/or making arrangements for hotel accommodation and food near the test site.
- 3. The applicant shall provide drinking water to the AMTEC Staff during the testing activity.
- 4. The applicant shall provide any form of shed or sunshade (e.g. tent, umbrella, etc.) for the test equipment, samples (if applicable) and AMTEC Staff during the testing activity in the field.
- 5. The applicant is requested to assist the AMTEC Staff in finding any means to access a safe and convenient restroom near the test site during the testing activity.

■ Testing Fee

- 1. The testing fee for walking-type agricultural tractor is PhP 19,500.
- 2. To proceed through AMTEC test, the test applicant shall settle at least 50 % of the testing fee which is non-refundable but transferrable.
- 3. In cases of additional testing during the field, the test applicant shall immediately pass the required documents and settle at least 50% of the testing fee within 5 working days after the testing proper.
 - ☐ Additional testing, number of machines: _____
- 4. Payment/s shall be directed to the following:
 - ☐ Through UPLB Cashier's Office (8AM to 12PM): AMTEC Trust Fund Code No. 8271632-40A2040101000 ☐ Through Landbank (8:30AM to 3PM): UPLB Trust Fund Account No. 1892100507 or UPLB FI Account No. 1892-1003-29

Other Reminders

- All manufacturers, fabricators, assemblers, and importers (MFAI) shall secure a Certificate of Conformity (CC) from the Bureau of Agricultural and Fisheries Engineering (BAFE) which guarantees that their agricultural and fisheries machinery conforms with PNS/BAFS PABES or other relevant standards identified by BAFE. More information about the application for CC can be found at http://bafe.da.gov.ph/index.php/certificate-of-conformity-of-manufacturers-fabricators-assemblers-distributors-dealers-importers-and-exporters/.
- 2. All MFAI shall employ an Agricultural and Biosystems Engineer (ABE), as mandated by RA 10915 (ABE Law), who shall facilitate all activities and concerns pertinent to AMTEC testing and BAFE requirements. Do you currently have an ABE in your roster of employees?

 Yes No