

# ACR 003:2024 CHECKLIST AND REMINDERS FOR THE AMTEC TEST CONDITIONS AND REQUIREMENTS FOR WALKING-TYPE AGRICULTURAL TRACTOR (PULL-TYPE)

# ■ Application for AMTEC Test

The applicant shall submit personally, through a courier, via email, or through Google Forms the duly accomplished and signed AMTEC-OP-F01 (Agricultural Machinery Test Application Form) to AMTEC. The Google Form link is available via the AMTEC website and its social media account. The application form must be accompanied by a document (e.g., operator's manual brochure) containing complete specifications as indicated in Annex B of PNS/BAFS 348:2022. A picture of the machine's nameplate and its prime mover's nameplate shall also be submitted with the application documents.

Location: Roberto C. Bautista Hall, CEAT, Pili Drive, University of the Philippines Los Baños, Los Baños, Laguna

Email: amtec.uplb@up.edu.ph Website: amtec.ceat.uplb.edu.ph

Facebook: https://www.facebook.com/amtec.uplb

## Preparation and Operation of the Machine

As recommended by AMTEC, the laboratory performance test shall be performed first. During laboratory performance test, AMTEC shall handle and operate the machine during the laboratory testing proper.

During field performance test, the same tractor (including the engine) tested in the laboratory shall be assembled and tested for normal operation. The officially designated representative and/or operator of the test applicant shall operate, demonstrate, adjust, repair, and decide on matters related to the operation of the machine. The operator shall be skilled in operating a float-assist type walking-type agricultural tractor.

### ■ Running-in of the Machine

A test run shall be conducted prior to the official test to check its condition and make necessary adjustments to the machine. During field performance test, no other adjustments shall be permitted while the official test is on-going.

### ■ Test Plot

he	e test applicant shall prepare at least two (2) test plots. Each test plot:
	☐ Shall be at least 500 m² to the edges and rectangular with sides in the ratio of 2:1 as much as possible;
	☐ Shall be unplowed and soaked for at least 24 hours for lowland field with water level of 3 cm to 5 cm;
	and
	□ Shall be unplowed for upland field.
	Other Test Necessities
he	e following shall also be adequately supplied during the conduct of the laboratory performance test:
	□ Sufficient engine and gear oil; and
	☐ Appropriate belt/s size for the transmission system.

The following shall also be adequately supplied during the conduct of the field performance test:

- ☐ Fuel tank of engine filled to full capacity;
- ☐ 4 L or sufficient fuel for refilling after each test trial; and
- □ Tools for machine repair and adjustments.

# ■ Machine Setting

The tractor shall be tested at the manufacturer's and the following recommended setting during rotary tilling operation:

- □ Operating width, mm: at least 150
- □ Operating depth, mm: 90-110



_	•				•					п	
	ĸ	_	а		и	-		ıe	n		œ
_	N	c	ч	v	ш	C	ш	ı	ш	u	9

AMTEC shall conduct various tests and verification on different parameters of the machine including the following requirements as per PNS/BAFS 345:2022:

■ Fabrication Requirements					
Item	Requirement as per PNS/BAFS 345:2022				
General	☐ The tractor shall be generally made of steel bars and sheet metals.				
Chain and Sprocket Transmission System	<ul> <li>Shall conform to PAES 303:2000 (Engineering materials – Roller chains and sprockets for agricultural machines – Specifications and applications)</li> <li>Shall have provisions for refilling of lubricating oil.</li> </ul>				
Hand Grip	☐ Shall be made of non-slip material ☐ Shall have a minimum nominal diameter of 25 mm.				
Handle Bar	<ul> <li>☐ Mechanism for handle bar height adjustment with at least three settings shall be provided.</li> <li>☐ Handle bar height shall be 650 mm to 800 mm.</li> </ul>				
Engine Speed	☐ Mechanism for adjustment of engine speed during operation shall be provided and within reach of the operator.				
Stand Assembly	☐ Shall be provided.				
Hitch	☐ Shall be in accordance with the specifications of PAES 107:2000 (Agricultural machinery – Hitch for walking-type agricultural tractor – Specifications).				

Basic hand tools as recommended by the manufacturer and separate basic tools for the engine shall be provided. The sizes of the hand tools shall be specified in metric units and shall be based on the applicable sizes required for operation and maintenance of the WTAT. These tools shall be suitable to the necessary

adjustment operations during maintenance and operation.						
■ Safety, Workmanship, and Finish						
Item	Requirement as per PNS/BAFS 345:2022					
General	<ul> <li>□ There shall be earmuffs or other ear protection device provided for the operator to use when 95 dB(A) is exceeded during operation. Recommendations for use of ear protection device shall likewise be indicated in the operator's manual.</li> <li>□ Shall be free from any manufacturing defects that may be detrimental to its operation.</li> <li>□ All metal surfaces shall be painted properly.</li> <li>□ Shall be free from sharp edges and rough surfaces.</li> <li>□ Appropriate labels, safety symbols, and warning notices shall be provided in accordance with PNS/BAFS 330:2022 (Technical means for ensuring safety – Guidelines).</li> <li>□ All controls shall be in accordance with PNS/BAFS 330:2022 (Technical means for ensuring safety – Guidelines).</li> <li>□ Shall be provided with heat shield or protection to minimize the possibility of inadvertent contact with the operator.</li> <li>□ Mechanism for emergency stop of the engine and immediate load disengagement of the transmission system shall be provided.</li> <li>□ Mechanism for belt transmission adjustment shall be provided.</li> <li>□ Belt cover and mud guard shall be provided. All other moving parts shall have safety guards.</li> <li>□ There shall be a provision for means to minimize vibration.</li> </ul>					



	<ul> <li>□ The hexagonal axle shall be in accordance with the specifications of PAES 108:2000 (Agricultural machinery – Hexagonal axle and hub for walking-type agricultural tractor – Specifications).</li> <li>□ The axle shall be able to accommodate compatible pneumatic tires provided for transport.</li> </ul>			
■ Performance Requirements				
Criteria	Requirement as per PNS/BAFS 345:2022			
Power requirement of the prime mover, kW, maximum	13.5			
Peak Transmission Efficiency, %, minimum	85			
Actual Field Capacity, ha/h	As per manufacturer's specification			
Breakdowns/malfunctions during the five-hour continuous running test	Shall have none			

# ■ Suspension and Termination of Test

If the machine stops due to breakdown or malfunction during the test run affecting the machine's performance, the test may be suspended. If the machine cannot continue the operation, the test shall be consequently terminated.

If the test plot does not conform with the recommended quantity and characteristics, AMTEC shall not proceed with the test. Should the test applicant request the conduct of the test despite the non-conformity to the test requirements identified by AMTEC, the applicant shall sign the AMTEC Waiver for Nonconformity to Test Requirements.

☐ AMTEC-OP-F24 (Waiver for Nonconformity to Test Requirements)

### ■ Other Assistance During Test

- 1. For field and laboratory tests outside the AMTEC premises, the applicant shall shoulder the transportation (i.e. fuel, toll fees, vehicle rental, plane fare, sea fare, etc.), food, and accommodation expenses of the AMTEC Staff assigned for the testing activity in accordance with the Terms and Conditions under the duly accomplished and signed AMTEC-OP-F1 (Agricultural Machinery Test Application Form).
- 2. The applicant shall provide drinking water for the AMTEC Staff during the testing activity.
- 3. The applicant shall provide any form of shed or sunshade (e.g. tent, umbrella, etc.) for the test equipment, samples (if applicable) and AMTEC Staff during the testing activity in the field.
- 4. The applicant is requested to assist the AMTEC Staff in finding any means to access a safe and convenient restroom near the test site during the testing activity.

## Testing Fee

- 1. The testing fee for walking-type agricultural tractor is PhP 29,250.
- 2. To proceed through AMTEC test, the test applicant shall settle at least 50 % of the testing fee which is non-refundable but transferrable.
- 3. In cases of additional testing during the field, the test applicant shall immediately pass the required documents and settle at least 50% of the testing fee within 5 working days after the testing proper.
  - ☐ Additional testing, number of machines: \_\_\_\_\_
- 4. Payment/s shall be directed to the following:
  - ☐ Through UPLB Cashier's Office (8AM to 2PM): AMTEC Trust Fund Code No. 8271632-40A2040101000
  - ☐ Through Landbank (8:30AM to 3PM): UPLB Trust Fund Account No. 1892100507



# Other Reminders

- 1. All manufacturers, fabricators, assemblers, and importers (MFAIs) shall secure a Certificate of Conformity (CC) from the Bureau of Agricultural and Fisheries Engineering (BAFE) which guarantees that their agricultural and fisheries machinery conforms with PNS/BAFS PABES or other relevant standards identified by BAFE. More information about the application for CC can be found at <a href="http://bafe.da.gov.ph/index.php/certificate-of-conformity-of-manufacturers-fabricators-assemblers-distributors-dealers-importers-and-exporters/">http://bafe.da.gov.ph/index.php/certificate-of-conformity-of-manufacturers-fabricators-assemblers-distributors-dealers-importers-and-exporters/</a>.
- 2. All MFAIs shall employ an Agricultural and Biosystems Engineer (ABE), as mandated by RA 10915 (ABE Law), who shall facilitate all activities and concerns pertinent to AMTEC testing and BAFE requirements. Do you currently have an ABE in your roster of employees? 

   Yes No